

33.70Mtr 4500BHP TUGBOAT 'ALMOAYYED 24' TWINSCREW TOWING TUG



General

Twin Screw Towing Tug Built for worldwide tows and mooring assistance

CLASS

LIQUID STORAGE

Classification Society E	3 V	
--------------------------	-----	--

Class Notain 1 + Hull, +Match, Tug

Unrestricted Navigation

Builder Wuxi Shipyard

P.R.CHINA

Year Built April 2007

MEASUREMENT

Length Overall33.70mLength B.P.30.00mBeam Moulded10.60m

Depth Moulded 4.00m Draft Designed 3.20m

TONNAGE

GRT 452ton NRT 135ton

CARGO DECK

Cargo Deck Area 95m2

Deck Strength 81.6 ton/m2.

Capacities

Fresh Water tank/Ballast Tank

Fresh Water Tanks 99M/T /99ton

Fuel Oil Tanks 272mt Lub Oil Tank 5.7mt Dirty Oil Tank 7.8mt

ACCOMMODATION

Cabins 2 x1berth cabins: 2 men

1 x1 berth cabins: 2 men 2 x 4 berth cabins: 8 men Complement 12 men

SPEED & BOLLARD PULL

Speed 12.5knots (Free running) Total Bollard Pull 57.17tonnes

Endurance 22days



33.70Mtr 4500BHP TUGBOAT 'ALMOAYYED 24' TWINSCREW TOWING TUG



General

Twin Screw Towing Tug Built for worldwide tows and mooring assistance

LOAD/DISCHARGE

TOWING & ANCHOR HANDLING EQUIPMENT

Connections Fuel Oil Female – 2 ½" Kamlock Portable Water Female - 2 1/2" Kamlock

CARGO DISCHARGE CAPACITY Fuel / Gas Oil / 2m...hr at 60m head

PROPULSION AND MANUVERING

Main Engines Caterpillar 2 x 2260BHP @1600RPM total 4519BHP

AH/Towing Winch Shipneed 24000MT @m/min. 30tons Brake / 120Tons Pull

Single Drum Electro Hydraulic driven Drum Capacity: 650m of 48mm dia.

DECK EQUIPMENT

Anchor Windlass 2.7ton @ 10m/min,

Brake holding @75ton.

Anchor 2 x stockless bower anchors

790kg each

Chain 258m x 28mm dia Grade U2

Propellors 2x4Bladed, approx 2444mm dia Stud ling chains

2444 x fixed pitch 4 -bladed

ELECTRIC POWER GENERATION FIRE FIGHTING EQUIPMENT **Diesel Generator** CO2 flooding system Engine Perkins CAT 3406TWGM 2 x 260KW

Fireman outfit 1 complete set

Diesel Driven Alternator, 380VAC/50Hz/3Ph Emergency fire pump 0.517m3/hrx25m head.